



TM-28E...600A Autoranging True-Rms AC/DC Clamp Meter + Watts



CAT III 600V

Features/Benefits

- 3-3/4 digit LCD, Backlit Display with maximum reading of 4000.
- High-speed bargraph.
- True-Rms.
- Watt measurement: 400KW
- Data Hold, Peak Hold, Min/Max, and Zero functions.
- AC/DC volts, AC/DC current, Resistance, Frequency, Watts, Continuity.
- Autoranging.
- Relative (REL) zero adjust.
- Maximum conductor size 35mm.
- Low battery indication.
- Overload indication.
- Continuity buzzer.
- Auto power off.

Specifications

Maximum Current	600 Amps
Display	4000 counts
Max. Conductor Size	35mm
AC Current	0.1A to 600A, $\pm(2.0\%$ of rdg + 5 dgts)
AC Voltage	0.1V to 600V, $\pm(1.2\%$ of rdg + 7 dgts)
DC Current	0.1A to 600A, $\pm(1.5\%$ of rdg + 5 dgts)
DC Voltage	0.1V to 600V, $\pm(1.0\%$ of rdg + 3 dgts)
Resistance	1 Ω to 4000 Ω ,
Continuity Buzzer	Yes
Frequency	1Hz to 400KHz
AC/DC Watts	0.1W to 400KW, $\pm(5.0\%$ of rdg + 5 dgts)
Backlit Display	Yes
Autorange	Yes
High Speed Bargraph	Yes
Auto Power Off	Yes
Min/Max	Yes
REL (zero adjust)	Yes
Data Hold and Peak Hold	Yes
Dimensions	218mm (L) x 75mm (W) x 43mm (D)
Weight	375g